



## Colibri Static Cling Film

Solvent-free, age-resistance, permanent elastic acrylic glue. Dot-shaped glue makes the material easier to handle and to reposition. Double sides PE coated photo paper as liner makes high rigidity and flat surface. Suitable for Eco-solvent, solvent, Latex, UV ink. Easily remove and reposition without glue residue. Film are used for wide range of smooth and slightly curved surface, for window decoration.

PVC Film: Glossy Monomeric PVC film, 100 micron, White

Adhesive: Permanent dot-shaped acrylic glue

Liner: Double Sides PE coated Photo Paper, 160gsm

Test Items	Units	Test method	Average value
Thickness-PP	Micron	GB/T6672-2001	190±10
Whiteness	%	GB4669-1995	≥88
Opacity	%	GB8807-88	990
Dimensional Stability-MD	mm		≤1.5
Dimensional Stability-CD	mm		≤0.8
Tensile Strength-MD	N/25mm	GB/T1040.1-2006	≥50
Tensile Strength-CD	N/25mm	GB/T1040.1-2006	≥40
Service Temperature	°C		-20-+70
Best Printing Temperature	°C		23±2; 50±5%RH
Ink temperature	°C		18-28
Preheating temperature	°C		30
Shelf Life	Stored at 20-25 °C/50-55 % RH		1 year
Durability, unprinted	Vertical exposure		1 year
*Testing condition: Indoor temperature 23°C, Relative Humidity 50%.			

